


OASYS OCP310M SERIES CARD PUNCHES



OCP 313M SEMI-AUTO SHEET FEED WITH SHINGLING CARD EXIT CONVEYOR

OCP310M SERIES PUNCH

- Unique double registration 3 axis alignment for highest punch accuracy
- Automated sheet registration on each punch stroke
- Proven industry track record
- Can be configured to wide range of sheet formats
- Quick tool change
- User friendly touch screen control man/machine interface
- All tooling made in-house
- Supplied with shingling card exit conveyor facility




Shingling Exit conveyor



Oasys in house tooling

Specifications

General: Safety: All Oasys machines are CE certified and comply with relevant European safety requirements including emergency stops and interlocked guarding.



OCP 313M SEMI-AUTOMATIC SHEET FEED WITH SHINGLING CARD EXIT CONVEYOR

TYPICAL SPECIFICATION FOR THE OCP313A CONFIGURATION

- Output up to 14,500 cards per hour
- Electrical: 220V OR 400V, (+/- 5%) 50 OR 60Hz, 3 Ph, 3 KVA
- Pneumatics: 114 litres/min @ 5.5 bar (4 CFM @80 psi)
- Machine Weight: Packed 1030 kgs approx
- Machine Dimensions: Packed L2400 x W1880 x H1560 mms

Note: OCP310 SERIES AVAILABLE AS 1-UP, 2-UP, 3-UP AND 4-UP

- * Specifications are subject to change without notification.
- * Actual output rates will be dependent upon product used, settings and configurations.

For further Information:

OASYS TECHNOLOGIES LTD, Unit 3 Stratton Business Park, Montgomery Way, Biggleswade, Bedfordshire, UK, SG18 8UB

Tel: +44 (0) 1767 600232 Fax: +44 (0) 1767 601532 E-mail: sales@oasys.uk.com Website: www.oasys.uk.com